

# **PRIMA IDRO** ® DRAINING CONCRETE OUTDOOR CONTINOUS FLOORING





Prima Idro®

ECO-SUSTAINABLE CEMENTITIOUS DI WHERE PRODUCT TECHNICAL DATA STRATIGRAPHIES & SOLUTIONS BENEFITS COLOR RANGE

DRAINING CONCRETE, THE GREEN SOLUTION.

ORAINING SYSTEM	5
	6
	9
	10
	12
	14



WATER PASSES THROUGH CONCRETE.



### ECO-SUSTAINABLE CEMENTITIOUS DRAINING SYSTEM

When it comes to designing or renovating the outdoor floor of a public or private space, be it a square, a pedestrian area, a public park or common areas paths within flat complexes, the most complicated aspect of the design is choosing the **most appropriate material and measures to drain rainwater**.

Essentially, right from the idea is to choose **certified materials** at the design stage that **concretely contribute** to improving outdoor spaces, avoiding as much as possible the creation of new impemeable (such as asphalt and concrete) and/or unstable (such as self-locking and loose gravel) surfaces.

Draining concrete, as the word implies, is a very porous concrete that is permeable to liquids. These floors are an ecologically sustainable solution to solve the problems related to the new development or upgrade of some urban areas, compatible with the values of respect and protection of the environment, by naturally helping the reintegration of groundwater and reducing the inflow of the same to the road surface.

All parties must be aware that during installation, concrete may have grout in the mixture.

The operating mechanism is simple: the water that arrives at the surface of Prima Idro® passes through the entire structure, reaches the subsoil and regenerates the groundwater. Part of the water is returned to the environment through evaporation, improving the thermohygrometric conditions of the site.

Prima Idro® effectively meets the requirements of sustainability and stability over time, allowing a drastic reduction in water collection structures, reducing the overall cost of the project, construction and subsequent maintenance.

## PRIMA IDRO®



### WHERE

Prima Idro® respects the environment and guarantees complete permeability. It is an environmentally sustainable solution applicable in various contexts:

- Drainage of road surfaces
- Pedestrian and bicycle paths
- Secondary and access roads
- Alleys and roads in areas of nature conservation or historical interest
- Paths near sports facilities and golf courses
- Parking areas
- Industrial and commercial yards





PERMEABLE AND DRAINING SURFACE.



- Medium thickness
- Color
- Max diameter aggregate
- Compression resistance at 28 days
   UNI EN 12930-3
- Fresh density
- Porosity
- Draining capacity (medium value) UNI EN 12697-40
- Free surface area (draining)
- Free surface area (draining)
- Material Yield
- Product appereance

\* Depending on the type and level of constipation achieved \*\* Value for average constipation

Frost

Resistance





Draining System

Non-slip

## PRODUCT TECHNICAL DATA

```
10 cm pedestrian - 15 cm driveable (car)
20 cm driveable (truck)
base color: natural gray, pigmentazione a ri-
chiesta.
from 6 to 11 mm - from 8 to 22
> 15 Mpa N/mm²
> 1650 kg/m³ about
≥ 15%
< 25%
5,78*10-3 m/s ≥ 150-180 liters/m²/minute
≥ 20%
≥ 1Mpa
18 kg/m² spess. 1 cm** about
Bulk
```





### STRATIGRAPHIES





Draining Concrete - 10 cm Gravel thickness 3 cm Vel layer Layer 15-20 cm (Variable aggregate granulometry between 40-70 mm positioned in a pyramid shape) Geotextile Ground

Prima Idro<sup>®</sup> permeable concrete - Pedestrian and cycle path





Prima Idro<sup>®</sup> permeable concrete - Version for traffic.

### BENEFITS



#### COMPLETELY AND IMMEDIATELY DRAINING

The open-pored structure allows natural infiltration of rainwater into the subsoil. The minimum drainage rate of Prima Idro® is about150-180 liters / m2 / minute. The water table is regenerated.

#### ENVIRONMENTAL BENEFITS

Prima Idro® helps reduce pollutants in runoff water. Water is retained by the top of the roadway, preventing it from being carried into waterways. The maximum flow rate through the sewer system is reduced.

#### ECONOMIC BENEFITS

Prima Idro® is a valid alternative to the construction and subsequent maintenance of underground pipes for the collection, channeling and drainage of stormwater on paved surfaces, reducing the need for large cisterns by serving as a collection and retention area.

#### HEAT ISLAND EFFECT

The surface cools faster because the porous material facilitates the passage of air.

#### RESISTANCE AND SAFETY

Resistance to freeze-thaw cycles (snow-covered drainage concrete is able to eliminate it much faster than conventional flooring).

It significantly improves traffic safety during rain. High porosity allows faster melting of snow.

#### DRIVABLE AND PEDESTRIAN

It has high mechanical strength and is suitable for both pedestrian and vehicular traffic.

#### MAINTENANCE

Simple ordinary and extraordinary maintenance and lower operating costs.



IMPROVEMENT OF SURFACE QUALITY

# **COLOR RANGE**

Prima Idro $^{ extsf{R}}$  is available in natural grey or sample colors.



Natural Grey

Yellow



Brown

Red









Prima Idro® Secondary access road.



Prima Idro® Pedestrial path in residential area.



Prima Idro<sup>®</sup> Permeable concrete support, suitable for per draining natural gravel finishes like Prima Drain Stone<sup>®</sup>

### SOME OF OUR CUSTOMERS









### CONTACT DETAILS PAVIMENTI SPECIALI SRL

#### Milano - Sede operativa

Via Piemonte, 23/B – 20098 San Giuliano Milanese (MI) T +39 02.98282914

#### Torino - Uffici amministrativi

Via Vittorio Amedeo II, 19 10121 Torino T +39 011.0714790

#### info@primapavimenti.it www.primapavimenti.it

#### Switzerland

Pavimenti Speciali Srl - Talenture S.A. Riva Albertolli 1 6900 Lugano - Switzerland

